

DESCRIPTION	QTY
SMA PCB MT CONNECTOR	1
1x2x.1" SIP MALE HEADER	2
1x2x.1" SIP FEMALE SHELL	2
Molex female pins	4
3PIN STEREO JACK	1
1x6x.1" SIP socket	1
TWISTED PAIR WIRE	9"
PN2222	1
PN3906	1
2N7000	1
2N2222A or equivalent	1
40m crystal	1
LED	1
6.8 OHM BLU-GRY-GOLD	1
100 OHM BRN-BLK-GOLD	1
220 OHM RED-RED-BRN	1
1K OHM BRN-BLK-RED	2
2.2K OHM RED-RED-RED	1
4.7K OHM YEL-VIO-RED	1
10K OHM BRN-BLK-ORG	1
22K OHM RED-RED-ORG	1
47K OHM YEL-VIO-ORG	1
100 OHM TRIMMER POT	1
100pf 101 (.2" spacing preferred)	1

120pf 121 (.2" spacing preferred)	1
220pf 221 (.2" spacing preferred)	1
470pf 471 (.2" spacing preferred)	2
1000pf 102 (.2" spacing preferred)	1
.01uf 103 (.2" spacing preferred)	2
.1uf 104 (.2" spacing preferred)	6
22uf electrolytic	1
1uh BRN-BLK-GOLD	2
10uh BRN-BLK-BLK	1
22uh RED-RED-BLK	1
xmit pcb	1